



Fifth Wheel for Terminal Tractors


For ratings and capacities see specification tables below

Type approved to 94/20/EG when fitted with optional manual secondary lock

FEATURES

- High strength cast steel construction permitted operating temperature to - 40 degrees C
- Top surface machined to improve wear, steering and fit with Trailer Plate. Patented grease groove pattern for improved wear and durability and prepared for central lubrication system
- Air operated lock release mechanism
- Locks require only 140 kg to couple
- Available with brackets for electronic sensors to indicate locks closed

DIMENSIONS



SPECIFICATION - standard version

Part Number	Weight	GCW	Vertical Load	Max. Speed
FW3510-TR	120 kg	100000 kg	36000 kg	35 km/h



The load limits given are valid for operation with speed limited to 35 km/h maximum and for use on well maintained roadways and yards within distribution depots and

dockyard areas. Mounting must be carried out in accordance with Holland instructions


This unit is **not** intended for use on public highways

SPECIFICATION - with optional manual secondary lock

For use when occasional, short movements of the vehicle on the public highway are required

Part Number	Weight	D-Value	Vertical Load
FW3510-TR-EG	121 kg	150 kN	20000 kg

EC approved 94/20/EG Type Approval No. e1*94/20*0812






The manual secondary lock **MUST** be engaged for all movements on the public highway

Holland reserves the right, without prior notice, to change specifcations and dimensions

FW3510-TR FIFTH WHEEL - SPARE PARTS



ltem	Part No.	Qty	Description	ltem	Part No.	Qty	Description	
1 *	XA-10099	1	Camplate	17 * ^	32027	2	Hex nut	
2 *	XB-10035	1	Bolt	18 *	XA-10096	2	Cable tab (brass)	
3 *	XA-1507-1	1	Roller	19 * ^	38026	2	45 degree lube fitting	
4 *	XB-07431-KTL	1	Washer	20 *	31036	1	Bolt	
5 *	XA-09040-KTL	1	Camplate Spacer	21 *	XA-3542-R-T	1	Air Cylinder Assembly	
6 *	XB-1505-KTL	1	Yoke Spring	22 *	XB-10087-KTL	1	Extension Spring - Inner	
7 *	XA-1706-1	1	Yoke Shaft	23 *	XB-10088-KTL	1	Extension Spring - Outer	
8 *	XA-10094	1	Yoke	24 *	38009	2	Lube Fitting	
9 *	XB-76004	2	Washer	25 *	XB-02967	1	Never-Seez Lube (not shown)	
10 *	XB-HLN-M12-Z	2	Locknut (Alt. part 32001)	26	XA-76020-KTL	1	Sensor Bracket	
11 *	31039	1	Bolt	27	XB-10210	2	Pocket Insert	
12 *	XA-1029	1	Roller	28	XB-2149-KTL	1	Spring	
13 *	XB-07628-KTL	1	Spring	29	XB-21-S-500-2750	1	Roll Pin	
14 *	`XA-07296-KTL	1	Lock Set	30	XA-3528-KTL	1	Secondary Lock Bar	
15 *	XA-E-60043	2	Lock Pin	31	XA-3546	1	Handle - Secondary Lock	
16 *	33027	1	Washer	32	XB-76022	1	Air cylinder clevis	
*	RK-3510-TR		Full Overhaul Kit, does not include items 26-31					
	RK-3510-TR-2		Overhaul kit excluding air cylinder, parts as for RK-3510-TR except does not include items 10, 20 and 21					
^	RS-91103		Lock repair kit, includes items 14, 15, 16, 17 and 19					
	RS-91110		Front Lock Grease Tube Kit					



SAF-HOLLAND GmbH

Hauptstraße 26 D-63856 Bessenbach, Germany Phone: +49 (0) 6095-301302 Fax: +49 (0) 6095-301200

HOLLAND EUROHITCH Ltd.

Hoo Farm Ind. Est. Worcester Rd. Kidderminster, Worcs. DY11 7RA, UK Phone: +44 (0) 1562-732010 Fax: +44 (0) 1562-732020

HOLLAND EUROPE GmbH

Altenkamp 9, D-33758 Schloss Holte-Stukenbrock, Germany Phone: +49 (0) 5207-89560 Fax: +49 (0) 5207-895656

Copyright © July 2007-SAF-HOLLAND. All information contained in this document is correct at time of copyright and is subject to change without notification all rights reserved